


Perskoppelingen X serie

SAEJ516


GSS Artikel nr	Slangmaat			Draad	Afmetingen (mm)					Max W.P.		
	DN	Size	Inch	F	H	L	S				bar	PSI
X02NM03	5	03	3/16"	1/8"-27	20,6	45,6	12				415	6000
X04NM03	5	03	3/16"	1/4"-18	26,5	51,5	14				415	6000
X02NM04	6	04	1/4"	1/8"-27	21,1	49,1	12				450	6500
X04NM04	6	04	1/4"	1/4"-18	27	55	14				450	6500
X06NM04	6	04	1/4"	3/8"-18	28,6	56,6	19				450	6500
oa X08NM04	6	04	1/4"	1/2"-14	34	62	22				415	6000
X04NM05	8	05	5/16"	1/4"-18	27	55	14				350	5000
X06NM05	8	05	5/16"	3/8"-18	28,6	56,6	19				350	5000
oa X08NM05	8	05	5/16"	1/2"-14	34	62	22				350	5000
X04NM06	10	06	3/8"	1/4"-18	27,5	58	16				450	6500
X06NM06	10	06	3/8"	3/8"-18	28,6	59,1	19				450	6500
X08NM06	10	06	3/8"	1/2"-14	34	64,5	22				415	6000
X06NM08	12	08	1/2"	3/8"-18	30,6	63,6	22				415	6000
X08NM08	12	08	1/2"	1/2"-14	35	68	22				415	6000
X12NM08	12	08	1/2"	3/4"-14	36,9	69,9	27				350	5000
X08NM10	16	10	5/8"	1/2"-14	36,2	72	25				350	5000
X12NM10	16	10	5/8"	3/4"-14	37,1	72,9	27				350	5000
X08NM12	20	12	3/4"	1/2"-14	37,5	78	27				350	5000
X12NM12	20	12	3/4"	3/4"-14	37,9	78,4	27				350	5000
X16NM16	20	12	3/4"	1"-11,5	45,5	86	35				280	4000
X12NM16	25	16	1"	3/4"-14	40,4	91,4	32				280	4000
X16NM16	25	16	1"	1"-11,5	47	98	35				280	4000
oa X20NM16	25	16	1"	1 1/4"-11,5	51,1	102,1	46				210	3000
X20NM20	32	20	1 1/4"	1 1/4"-11,5	51,9	109,6	46				210	3000
X24NM24	40	24	1 1/2"	1 1/2"-11,5	55	119,5	50				185	2700
X32NM32	50	32	2"	2"-11,5	64	134	65				165	2400



3

NPSM

GSS Artikel nr	Slangmaat			Draad	Afmetingen (mm)					Max W.P.		
	DN	Size	Inch	F	H	L	S				bar	PSI
X04NSF04	6	04	1/4"	1/4"-18	19	47	17				350	5000
X06NSF06	10	06	3/8"	3/8"-18	21	51	22				280	4000
X08NSF08	12	08	1/2"	1/2"-14	23	56	25				240	3500
X12NSF12	20	12	3/4"	3/4"-14	27	67	32				240	3500
X16NSF16	25	16	1"	1"-11,5	30	81	38				210	3000



Gekrompen moer